

Courtesy of: □
Aquadepot® □
888-242-4500 □
www.aquadepot.com □



Ceramic Filters Company, Inc.

A-2 Fluoride Reduction Element


A-2 Fluoride Reduction Water Filter Element

These filter elements are designed to reduce fluorides in drinking water to below 0.5 ppm. They are constructed with materials which are FDA approved. They cannot be regenerated.

The A-2 filter element uses activated alumina that has been especially prepared for the reduction of fluorides in drinking water. Laboratory tests show that this preparation will improve the capability of the filter to reduce the fluoride levels from 10 ppm F+ to below 0.2 ppm F+. Normal total capacity of the A-2 is over 8,000 ppm F+.

Performance of the A-2 will be degraded by flow rates in excess of 0.25 g.p.m., high pH (alkaline) or high bicarbonate supply water. If the supply water tests above 100 ppm of bicarbonate, the fluoride reduction will be degraded to less than 50%; if the supply is over 200 ppm, the reduction efficiency is less than 75% of normal.

The A-2 has also been shown to reduce arsenic to less than 0.02 ppm from 0.12 ppm in the supply water. Total capacity for arsenic has not been determined.



SIZE:

10" (Fits all Doulton housings)

COLOR:

White

POST FILTER:

50 Micron spun-bonded polypropylene

SPONGE RETAINER

MEDIA:

400 grams of prepared activated alumina

PRE-FILTER:

100 Micron spun-bonded polypropylene